

LISTING OF THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. - 3. (Canceled)

4. (Currently Amended) An endoscope apparatus comprising:

a general-purpose video processing circuit having a drive signal generation function for driving a solid-state image pick-up device built into an endoscope and a signal processing function for outputting a standard video signal by processing an output signal from the solid-state image pickup device; and

d an endoscopic function adjusting circuit comprising a function modifying circuit, connected to the general-purpose video processing circuit, for modifying at least one of the drive signal processing function and the signal processing function executed by the general-purpose video signal processing circuit in accordance with the endoscope having the solid-state image pickup device therein;

wherein the endoscopic function adjusting circuit comprises a delay amount adjusting circuit for canceling the effect of a signal delay taking place in a signal cable connecting the solid-state image pickup device to the signal processing circuit, by adjusting ~~signal timings~~ timing of drive signals of the solid-state image pickup device.

5. (Withdrawn) An endoscope apparatus comprising:


a general-purpose video processing circuit having a drive signal generation function for driving a solid-state image pick-up device built into an endoscope and a signal processing function for outputting a standard video signal by processing an output signal from the solid-state image pickup device; and

an endoscopic function adjusting circuit comprising a function modifying circuit, connected to the general-purpose video processing circuit, for modifying at least one of the drive signal processing function and the signal processing function executed by the general-purpose video signal processing circuit in accordance with the endoscope having the solid-state image pickup device therein;

wherein the endoscope is detachably connected to a light source, and the endoscopic function adjusting circuit comprises at least a white balance adjusting circuit for detecting ID information indicative of the wavelength distribution of light emitted by a lamp built into the light source, and automatically setting a white balance state in view of said ID information.

6. **(Withdrawn)** An endoscope apparatus comprising:

a general-purpose video processing circuit having a drive signal generation function for driving a solid-state image pick-up device built into an endoscope and a signal processing function for outputting a standard video signal by processing an output signal from the solid-state image pickup device; and

 an endoscopic function adjusting circuit comprising a function modifying circuit, connected to the general-purpose video processing circuit, for modifying at least one of the drive signal processing function and the signal processing function executed by the general-purpose video signal processing circuit in accordance with the endoscope having the solid-state image pickup device therein;

wherein the endoscopic function adjusting circuit comprises an adjusting circuit accommodating a variation in the number of pixels, for producing the standard video signal, even when the number of the pixels in the solid-state image pickup device is changed, by storing dummy pixels in a frame memory to compensate for a reduced number of pixels, and by applying a zoom function to produce said standard video signal from said reduced number of pixels.

7. **(Withdrawn)** An endoscope apparatus according to Claim 6, wherein the endoscopic function adjusting circuit has the function of outputting a video signal which produces a still image.

8. **(Withdrawn)** An endoscope apparatus comprising:
a general-purpose video processing circuit having a drive signal generation function for driving a solid-state image pick-up device built into an endoscope and a signal processing function for outputting a standard video signal by processing an output signal from the solid-state image pickup device; and
an endoscopic function adjusting circuit comprising a function modifying circuit, connected to the general-purpose video processing circuit, for modifying at least one of the drive signal processing function and the signal processing function executed by the general-purpose video signal processing circuit in accordance with the endoscope having the solid-state image pickup device therein;
wherein the endoscopic function adjusting circuit has the motorized function of flexing a bending portion of the insert section, interlocked with pan and tilt display functions which compensate for said motorized bending operation.

9. **(Previously Presented)** An endoscope apparatus according to Claim 4, wherein the general-purpose video signal processing circuit and the endoscopic function adjusting circuit are usable with a plurality of insert sections having different respective lengths and correspondingly different internal delay amounts.

10. **(Previously Presented)** An endoscope apparatus according to Claim 4, wherein the general-purpose video signal processing circuit and the endoscopic function adjusting circuit are usable with a plurality of solid-state image pickups having different respective numbers of pixels.

11. **(Previously Presented)** An endoscope apparatus according to Claim 4, further comprising:
a solid-state image pickup device mounted at the end of an insert section of an endoscope;

a signal processing circuit, arranged in the endoscope, for driving the solid-state image pickup device and for producing a standard video signal in response to an output signal from the solid-state image pickup device;

Cl
and said general-purpose video signal processing circuit and said endoscopic function adjusting circuit being comprised in said signal processing circuit.

12. **(Previously Presented)** An endoscope apparatus according to Claim 4, wherein said endoscopic function adjusting circuit controls a wave-shaping operation for wave-shaping said output signal from said solid-state image pickup device.
